



# Floor Finish

With Built-in Microban® Antimicrobial Technology



FLOOR CARE

## Antimicrobial

Compatible with the  
Altra Lite Applicator

PROTECTION THAT LIVES ON  
**MICROBAN®**

Altra Floor Finish with Microban® technology maintains its high gloss with minimal maintenance. It is an extremely durable floor finish that is ideal when there is limited equipment or manpower for a buffing program. Altra Floor Finish with Microban technology is versatile and may be used on all porous floors.

Microban technology is built-in antimicrobial product protection that gives Altra Floor Finish an added level of proactive product protection against damaging microbes. Altra Floor Finish with Microban technology reduces the overall bacterial load, keeping floors cleaner, longer in your facility.\*



Clarity



Durability



Repairability

\*Microban technology does not protect users against disease-causing microorganisms. Microban Products Company makes neither direct nor implied public health claims. Normal cleaning practices should be maintained.

## Directions for use

### Floor Preparation:

1. Strip floor using Altra Low Odor Floor Stripper.
2. After picking up solution, rinse floor until no residue remains.
3. Allow floor to dry before applying Altra Floor Finish.

### Application:

1. Apply finish in even coats 750 sq. ft./48 oz.
2. Allow each coat to dry, usually 20 to 30 minutes.
3. Apply multiple coats until desired gloss is achieved.

### Using Altra Lite Applicator:

1. Use an Altra Lite applicator with a clean and rinsed microfiber finish mop.
2. Saturate microfiber finish mop with water and ring out prior to applying finish.

### Using Standard String Mop:

1. Use a clean mop and bucket with a new trash liner.
2. Saturate mop, press firmly into wringer to remove excess finish. Do not wring mop.

### Maintenance:

1. Dust mop floor.
2. Damp mop floor as needed, using Altra Multi-Purpose HP Cleaner.

**Available Packaging: 8 × 48 oz. bottle  
2 Gallon Mini Pac**

Altra Floor Finish Technical Specifications	
pH	8.6 ± 0.4
Leveling	Excellent
Freeze/Thaw Stability	Passes 3 cycles
Removability	Excellent
Drying Time	20–30 minutes
Black Mark Resistance	Excellent
Film Color	Water-Clear
Scrubability	Excellent
Weight/Gallon	8.56 lbs.
Slip Resistance	UL Classified

Made in USA

